

ETBH16E6V
 ETBH16E9W
 ETBX16E6V
 ETBX16E9W

Factory-mounted equipment for ·ETB(H/X)16EF*·

Description	ETB(H/X)16EF*	
	6V (8)	9W (8)
Heating only model ·ETBH·	6V (8)	9W (8)
Reversible model ·ETBX·	6V (8)	9W (8)
Backup heater ·2-4-6kW 1N-230 V·	o	-
Backup heater ·2-4-6kW 3-230 V·	o	-
Backup heater ·3-6-9kW 3N-400 V·	-	o

Outdoor combination table for ·ETB(H/X)16EF*·

Description		EPRA14DA(V3/W1)	EPRA16DA(V3/W1)	EPRA18DA(V3/W1)
ETBH16EF*	Heating only	o	o	o
ETBX16EF*	Reversible	o	o	o

Kit availability for indoor units

Reference	Description	ETB*16EF*	
		6V	9W
ETBH*	Heating only indoor unit	6V	9W
ETBX*	Reversible indoor unit	6V	9W
EKRP1HBAA	Digital I/O PCB	*(1)	(2)
EKRP1AHTA	Demand PCB	*(3)	o
BRC1HHDA*	HCI (Human Comfort Interface)	o	o
EKPCAB4	PC cable	*(4)	o
EKHWS150D3V3	Domestic hot water tank ·150 l 1-230 V·	o	o
EKHWS180D3V3	Domestic hot water tank ·180 l 1-230 V·	o	o
EKHWS200D3V3	Domestic hot water tank ·200 l 1-230 V·	o	o
EKHWS250D3V3	Domestic hot water tank ·250 l 1-230 V·	o	o
EKHWS300D3V3	Domestic hot water tank ·300 l 1-230 V·	o	o
EKHWSU150D3V3	Domestic hot water tank ·150 l 1-230 V·	o	o
EKHWSU180D3V3	Domestic hot water tank ·180 l 1-230 V·	o	o
EKHWSU200D3V3	Domestic hot water tank ·200 l 1-230 V·	o	o
EKHWSU250D3V3	Domestic hot water tank ·250 l 1-230 V·	o	o
EKHWSU300D3V3	Domestic hot water tank ·300 l 1-230 V·	o	o
EKHWP500B	Domestic hot water tank with solar connection	*(9)(10)	o
EKHWP500PB	Domestic hot water tank with solar connection	*(9)(10)	o
EKHWP300B	Domestic hot water tank with solar connection	*(9)(10)	o
EKHWP300PB	Domestic hot water tank with solar connection	*(9)(10)	o
EKHV3PART	Third-party tank connection kit for thermistor pocket	o	o
EKMIKPOA	Mixing kit - PCB only	o	o
EKMIKPHA	Mixing kit - PCB with hydraulics	o	o
EKMIKHMA	Hydraulics - mixed pump group	*(13)	o
EKMIKHUA	Hydraulics - unmixed pump group	*(13)	o
EKMIKBVA	Balancing vessel	o	o
EKMIKDIA	Distributor for balancing vessel	*(14)	o
KRCS01-1	Remote indoor sensor	*(5)	o
EKRSCA1	Remote sensor for outdoor	*(5)	o
EKCC8-W	Universal centralised user interface	o	o
DCOM-LT/IO	DCOM gateway	o	o
DCOM-LT/MB	DCOM gateway	o	o
BRP069A71	WLAN module	*(12)	o
ESAE04A01*	Daikin Residential Controller	o	o
EKRELSG	Relay for Smart Grid	o	o
EKHBCONV	Conversion kit: heating only to reversible.	o	o
AFVALVE1	Freeze protection valve	o	o
FWXV10-15-20ATV3*	Heat pump convector	*(6)	o
FWXT10-15-20ATV3*	Heat pump convector	*(6)	o
FWXM10-15-20ATV3*	Heat pump convector	*(6)	o
EKVKHPC	Heat pump convector valve kit	*(6)	o
EKRTWA	Wired room thermostat	o	o
EKRTR1	Wireless room thermostat	o	o
EKRTE5	External sensor room thermostat	*(7)	o
EKWUFHTA1V3	Multi-zoning base unit 230 V	*(11)	o
EKWCTRD1V3	Digital thermostat 230 V	*(11)	o
EKWCTRAN1V3	Analogue thermostat 230 V	*(11)	o
EKWCVATR1V3	Actuator 230 V	*(11)	o

Kit availability for outdoor units

Reference	Description	EPRA14DA(V3/W1)	EPRA16DA(V3/W1)	EPRA18DA(V3/W1)
EKMST1	Mounting stand	o	o	o
EKMST2	Mounting stand	o	o	o

Kit availability for domestic hot water tanks

Reference	Description	EKHWP*			
		500B	500PB	300B	300PB
EKHWP*	Domestic hot water tank with solar	o	o	o	o
EKSRPS4A	Solar pump station	o	o	o	o
EKEPRHLT3HX	Dedicated connection kit available.	o	o	o	o
EKEPRHLT5H	Heating only indoor unit	o	o	o	o
EKEPRHLT5X	Only for reversible models	o	o	o	o

Notes

- PCB that provides additional output connections:
 - Control external heat source (bivalent operation).
 - Output remote ON/OFF signal space heating/cooling
 - Remote alarm output
- Additional relays to allow bivalent control in combination with an external room thermostat are field-supplied.
- PCB to receive up to ·4· digital inputs for power limitation
- Data cable for connection with PC.
- Only 1 remote sensor can be connected: indoor OR outdoor sensor.
- The valve kit is mandatory if a heat pump convector is installed on a reversible model (not mandatory for heating only models).
- EKRTETS· can only be used in combination with ·EKRTR1·
- The backup heater capacity depends on a user interface setting.
- Solar pump station
- Dedicated connection kit available: ·EKEP*·.
- Multi-zoning wired controls
- The WLAN cartridge is supplied in the accessory bag of the unit and is meant to be plugged
- Only possible in combination with ·EKMIKPOA·
- Only possible in combination with ·EKMIKBVA· and ·EKMIKPHA· or ·EKMIKHUA·

Remark

Other combinations than mentioned in this combination table are prohibited.