



Model	AA	AB
RYMQ14-16T, RXYQQ14-16T, REYQ14-20T	240	205
RYMQ18-20T, RXYQQ18-20T	240	210

- Notes
- Detail A and detail B indicate the dimensions after fixing the attached piping.
 - Items 4 - 10: Knockout hole.
 - Gas pipe
 - REYQ14-20T : Ø 25.4 brazing connection
 - RYYQ14-20T, RYMQ14-20T, RXYQ14-20T, RXYQQ14-20T : Ø 28.6 brazing connection
 - Liquid pipe
 - RYYQ14-16T, RYMQ14-16T, RXYQ14-16T, RXYQQ14-16T, REYQ14-20T : Ø 12.7 brazing connection
 - RYYQ18-20T, RYMQ18-20T, RXYQ18-20T, RXYQQ18-20T : Ø 15.9 brazing connection
 - Equalising pipe
 - RYMQ14-16T : Ø 22.2 brazing connection
 - RYMQ18-20T : Ø 28.6 brazing connection
 - High pressure/low pressure gas pipe
 - REYQ14-20T : Ø 22.2 brazing connection

11	Grounding terminal	Inside of the switch box (-M8)
10	Pipe routing hole (bottom)	
9	Pipe routing hole (front)	
8	Power cord routing hole (bottom)	Ø65
7	Power cord routing hole (front)	Ø27
6	Power cord routing hole (front)	Ø65
5	Power cord routing hole (front)	Ø80
4	Power cord routing hole (side)	Ø65
3	Equalising pipe connection port	See note 3.
	High pressure/low pressure gas pipe	
2	Gas pipe connection port	See note 3.
1	Liquid pipe connection port	See note 3.
No.	Part name	Remark