



No.	Part name	Remark
1	Liquid pipe connection port	See note ·3·.
2	Gas pipe connection port	See note ·3·.
3	Equalising pipe connection port High pressure/low pressure gas pipe	See note ·3·.
4	Power cord routing hole (side)	Ø65
5	Power cord routing hole (front)	Ø80
6	Power cord routing hole (front)	Ø65
7	Power cord routing hole (front)	Ø27
8	Power cord routing hole (bottom)	Ø65
9	Pipe routing hole (front)	
10	Pipe routing hole (bottom)	
11	Grounding terminal	Inside of the switch box (·M8·)

Model	AA	AB
RYMQ14-16T, RXYQQ14-16T, REYQ14-20T	240	205
RYMQ18-20T, RXYQQ18-20T	240	210

NOTES

1. Detail ·A· and detail ·B· indicate the dimensions after fixing the attached piping.
2. Items ·4 - 10·: Knockout hole.
3. Gas pipe

RXYTQ10T	: Ø ·22.2· brazing connection
REYQ14-20T	: Ø ·25.4· brazing connection
RYYQ14-20T, RYMQ14-20T, RXYQ14-20T, RXYQQ14-20T, RXYTQ12-16T	: Ø ·28.6· brazing connection
Liquid pipe	
RXYTQ10T	: Ø ·9.5· brazing connection
RYYQ14-16T, RYMQ14-16T, RXYQ14-16T, RXYQQ14-16T, REYQ14-20T	: Ø ·12.7· brazing connection
RXYTQ12-16T RYYQ18-20T, RYMQ18-20T, RXYQ18-20T, RXYQQ18-20T	: Ø ·15.9· brazing connection
Equalising pipe	
RYMQ14-16T	: Ø ·22.2· brazing connection
RYMQ18-20T	: Ø ·28.6· brazing connection
High pressure/low pressure gas pipe	
REYQ14-20T	: Ø ·22.2· brazing connection